


Measuring Guide for Tailored Roman Shades



Double-check your work—always measure twice to ensure accuracy.

Tools and Tips

- Steel tape measure — do not use cloth tape
- Pencil
- Round measurements to the nearest 1/8"



Measuring Guidelines

Measuring for an Inside Mount			
Inside Mount: Window treatments are installed inside the window casing. Use a steel tape measure for taking measurements.	1. Measure Depth: See chart below to determine if window casing has enough depth for an inside mount window treatment.	2. Measure Width: Measure the inside width of window casing in three places; record narrowest measurement.	3. Measure Length: Measure the inside length from the top of window casing to the top of the sill in three places; record longest measurement.

NOTE: Do not take any deductions for clearance. The manufacturer will take necessary deductions for a perfect fit.

Fabric Shades Control Type	Minimum Depth Needed for Inside Mount (inches)	Depth Needed for Flush Mount ⁽¹⁾ (inches)
Standard Cord Control	3/4	2 3/8
Upturned Headrail ⁽²⁾	1 1/4	1
Continuous-Loop Lift	3/4	3 1/8
Motorized Lift	3/4	3 1/8
Cordless	See cordless size considerations chart on page 2	See cordless size considerations chart on page 2

(1) Flush mount includes headrail and fabric and is approximate. This can vary by fabric and shade style.

(2) For direct mount, front control shades add 3/4" to the mounting depths for clearance of the pleat tabs and rings. Upturned headrail is direct mount only; mounting brackets are not available.

Measuring for an Outside Mount			
Outside Mount: Window treatments are installed outside the window casing. Use a steel tape measure for taking measurements.	1. Determine Headrail Location: Determine if headrail will be on molding or above molding and mark the spot.	2. Measure Width: Measure exact width to be covered; we recommend 1 1/2" overlap on each side of the window (3" total) for optimum light control and privacy; record measurement.	3. Measure Length: Measure exact length to be covered, including desired overlap (typically from 1" above the molding to bottom of sill or apron); record measurement.

NOTE: The manufacturer makes no deductions on outside mount installations.

Measuring for a Relaxed and Balloon Shade	
Relaxed and Balloon Shade: Tend to "toe-in" at the bottom; inside mounts or multiple shades on one headrail are not recommended. Use a steel tape measure for taking measurements.	1. Measure Length: Measure to the short point on the bottom edge.

Cordless Shades: Looped Roman, Classic Flat Roman, Seamless Roman, Relaxed Roman

Minimum and Maximum Cordless Shades: Standard, Water Repellent, Thermal

NOTE: Minimum width 18", minimum length 18". Shaded area indicates headrail size, see below for details.

Length up to (inches) ↓	Width up to (inches) →													
	18	24	30	36	42	48	54	60	66	72	78	84	90	96
24														
30														
36														
42														
48														
54														
60														
66														
72														
78														
84														
90	N/A													
96	N/A													
102	N/A	N/A												
108	N/A	N/A												





Minimum and Maximum Cordless Shades: Blackout, Flannel-Back

NOTE: Minimum width 18", minimum length 18". Shaded area indicates headrail size, see below for details.

Length up to (inches) ↓	Width up to (inches) →													
	18	24	30	36	42	48	54	60	66	72	78	84	90	96
24														
30														
36														
42														
48														
54														
60														
66														
72														
78														
84														
90	N/A	N/A												N/A
96	N/A	N/A											N/A	N/A
102	N/A	N/A										N/A	N/A	N/A
108	N/A	N/A									N/A	N/A	N/A	N/A

NOTE: For all inside mount applications, 3/8" deduction is taken by the manufacturer on ordered width.

Depth Requirements for Inside Mount

	Headrail Dimensions (inches)	 Partially recessed headrail in window casing/molding	 Fully recessed headrail in window casing/molding
Cordless: Areas Shaded Dark 	1½ D x ⅝ L	Minimum Depth Mount (inches)	Flush with Casing ¹ (inches)
		¾	2¾
Cordless: Areas Shaded Light 	2¼ D x ⅝ L	¾	3¾

(1) Flush mount includes headrail and fabric and is approximate. This can vary by fabric and shade style.